

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

SECTION 1. IDENTIFICATION

Product identifier:	JAX Dry-Glide (Aerosol)		
Part number:	JAX108		
Identified uses:	Lubricant where there may be incidental food	contact	
Uses advised against:	Not intended for direct food contact. Other use	es advised against may be specifie	ed elsewhere in this SDS.
Supplier:	Pressure-Lube Inc. JAX W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA		
Email contact:	info@jax.com		
<u>Non-emergency</u> <u>contact:</u>	Phone: 262-781-7660 Fax: 262-781-390	6	
Emergency telephone:	INFOTRAC:		
	North America 1-800-535-5053 International 011-1-352-323-3500 (collect)	Australia 1-300-366-961 China 400-120-0761	Germany 0800-181-2926
	DENTIFICATION		

SECTION 2. HAZARD(S) IDENTIFICATION

Classification:	Flammable Aerosol Cat. 1
<u>Label elements</u> Pictograms:	
Signal word:	Danger
Hazard statements:	Extremely flammable aerosol.
Precautionary statements:	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Hazards not otherwise Not applicable. classified:

Additional information: Not applicable.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS **Impurities Composition: Chemical name** <u>%</u> <u>CAS #</u> Naphtha (petroleum), hydrotreated light* 50-100 64742-49-0 None Propane 10-25 74-98-6 None Butane 2.5-10 106-97-8 None

SECTION 4. FIRST-AID MEASURES

First aid measures	
Eye contact:	Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation persists, consult a physican.
Skin contact:	Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.
Ingestion:	If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation:	Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Most important symptoms and effects, both acute and delayed	No further relevant information available.
Indication of any immediate medical attention and special treatment available:	See First aid measures (above).

General information: No further relevant information available.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.
<u>Unsuitable</u> extinguishing media:	Do not use direct stream of water.
Specific hazards:	Extremely flammable aerosol. Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.
Advice for firefighters:	Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined space or as otherwise needed.
SECTION 6. ACCIDENTA	L RELEASE MEASURES
Personal precautions, protective equipment and emergency procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.
Environmental precautions:	Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.
<u>Methods for</u> <u>containment and</u> <u>cleaning up</u>	 Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal. Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

SECTION 7. HANDLING AND STORAGE

<u>Precautions for safe</u> <u>handling</u> :	Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 49°C (120°F). Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: (1) keep area ventilated, (2) do not smoke, (3) extinguish all flames, pilot lights and heaters, and (4) turn off stoves, electric tools and appliances, and any other sources of ignition. For industrial use only.
<u>Conditions for safe</u> storage, including any incompatibilities:	Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Observe official regulations on storing packagings with pressurized containers. Store away from oxidizing agents. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Rotate stock.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

	•		
Workplace exposure	Chemical name	Exposure limit and sou	irce
<u>limits:</u>	Naphtha (petroleum), hydrotreated light*	Not available	
	Propane	Not available	
	Butane	Long-term value = 1810) mg/m³, 750 ppm
		Short-term value = 145	0 mg/m³, 600 ppm
Exposure controls			
Engineering controls:	Provide exhaust ventilation or other engineering co occupational exposure limits.	ntrols to keep the airborne co	ncentration of vapors below their respective
Ventilation:	Use in a well-ventilated area. See Engineering Controls.		
Personal hygiene:	Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.		
Eye protection:	Chemical splash goggles or face shield in compliance	e with OSHA regulations are a	dvised when eye contact may occur.
Hand protection:	Any lined non-permeable rubber gloves.		
Respiratory protection	: Use with adequate ventilation. Respiratory protecti local exhaust ventilation to control exposure. In cas NIOSH/MSHA-approved air-supplied respirator is ac	e of insufficient ventilation, w	ear suitable respiratory equipment. A
SECTION 9. PHYSICAL AI	ND CHEMICAL PROPERTIES		
Appearance / odor:	Clear with solvent odor	Upper flammability limit:	Not available
		Lower flammability limit:	Not available
Physical state:	Liquid and compressed gas in aerosol can	Vapor pressure:	Not available

JAX Dry-Glide (Aerosol)				Page 3 of 4 Revision Date Supersedes Date	3/10/2016 7/30/2015
Odor threshold:	Not available	Vapor density:			
<u>рН</u> :	Not available		Not available		
Melting / freezing point	Not available	Relative density:	0.65 (typic	cal)	
Initial boiling point	Not available				
and boiling range:		Solubility in water:	Not availa	ble	
Flash point:	Not available; however, product is classified as an extremely flammable aerosol.	Partition coefficient (n-octanol/water):	Not availa	ble	
Evaporation rate:	Not available	Autoignition temperature:	Not availa	ble	
Flammability (solid, gas):	Extremely flammable aerosol	Decomposition temperature:	Not availa	ble	
<u></u>	,	Viscosity:	Not availa	ble	

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Not reactive under normal conditions.
Chemical stability:	Stable under recommended conditions.
Possibility of hazardous reactions:	Hazardous reactions are not expected to occur.
<u>Conditions and</u> materials to avoid:	Keep away from heat, sparks, open flames and other sources of ignition. Keep out of direct sunlight. Avoid strong oxidizers, strong alkalis and strong acids.
Hazardous decomposition products:	Carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

mormation on intervio	dies of exposure			
Eye contact:	No known significant effects or critical hazards.			
Skin contact:	No known significant effects or critical hazards.			
Inhalation:	No known significant effects or critical hazards.			
Ingestion:	No known significant effects or critical hazards.			
<u>Component</u>	Components	<u>LD₅₀</u>	<u>LC₅₀</u>	
information:	Naphtha (petroleum), hydrotreated light*	Not available	Not available	
	Propane	Not available	Not available	
	Butane	Not available	658 mg/l/4h (inhalation, rat)	
Information on physical	, chemical and toxicological effects			
Symptoms:	See Section 4 of this SDS for symptoms.			
Delayed and immediate	effects, and chronic effects, from short and long-terms	exposure		
Effects:	No further relevant information available.			
Carcinogenicity:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.			
<u>Numerical measures of</u> toxicity:	Not determined			
SECTION 12. ECOLOGICA	L INFORMATION			
Ecotoxicity:	Not available			
Component	Components	L(E)C ₅₀		
information:	Naphtha (petroleum), hydrotreated light*	Not available		
	Propane	Not available		
	Butane	Not available		
Persistence and degradability:	Not determined			
<u>Bioaccumulative</u> potential:	Not determined			

Mobility in soil: Not available

Other adverse effects: Not determined

SECTION 13. DISPOSAL CONSIDERATIONS

 Waste treatment
 Disposal

 methods:
 Consult r

Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	<u>UN Number</u> :	Hazard <u>Class:</u>	Packing <u>Group</u> :	Remarks:
<u>U.S. D.O.T.</u>	Aerosols, flammable	UN1950	2.1	None	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Aerosols, flammable	UN1950	2.1	None	Tunnel Restriction D
IMDG	Aerosols, flammable	UN1950	2.1	None	None
<u>IATA</u>	Aerosols, flammable	UN1950	2.1	None	None

SECTION 15. REGULATORY INFORMATION

U.S. Federal Regulations SARA Section 302 This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: **Extremely Hazardous** None Substances: SARA Section 304 Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to **CERCLA Hazardous** reporting to the National Response Center under CERCLA: Substances: None SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: Chemicals: None **TSCA Inventory:** All components of this material are on the U.S. TSCA Inventory. **U.S. State Regulations California Proposition** This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm. 65 Status: California None **Proposition 65** Listed Components:

International Regulations

Canada: This product has been classified in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the information required by those regulations.

Japan MITI:	Not available
Australia:	Not available
Switzerland:	Not available

SECTION 16. OTHER INFORMATION

Sections Revised:	Sections 2, 7 and 11.

Revision Date: 3/10/2016

The information and recommendations contained herein are, to the best of Pressure-Lube Inc. JAX's knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. JAX makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. JAX shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc. JAX's interpretation of the available data.