

# SAFETY DATA SHEET

**CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD** (HCS) 29 CFR 1910.1200

Page 1 of 5

**Revision Date** 6/1/2015 **Supersedes Date** 1/8/2014

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: **JAX BDF Cling-Lube (Aerosol)** 

JAX214 Part number:

1.2 Identified uses: Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

Pressure-Lube Inc. JAX 1.3 Supplier:

> W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

**Email contact:** info@jax.com

Non-emergency

contact:

Phone: 262-781-7660 Fax: 262-781-3906

1.4 Emergency telephone: INFOTRAC:

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

**SECTION 2. HAZARDS IDENTIFICATION** 

2.1 GHS Classification:

Hazard class(es): Aquatic Chronic Cat. 3

2.2 Label elements

Pictograms: Not applicable

Warning Signal word:

Hazard-determining

components of labeling:

Not applicable

**Hazard statements:** Pressurized container: May burst if heated. Harmful to aquatic life with long lasting effects.

**Precautionary** 

Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even statements: after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Avoid release to the environment.

Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Additional information 21.0 % by mass of the contents are flammable

2.3 Other hazards

Results of PBT and vPvB assessment Not applicable PBT: vPvB: Not applicable

# **SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS**

3.1 Composition	Components	<u>%</u>	CAS#	<u>Impurities</u>
	Propane	10-25	74-98-6	None
	Butane	1-5	106-97-8	None
	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	<1	148520-84-7	None
	Zinc oxide	<1	1314-13-2	None
Sulfonic acids, petroleum, calcium salts Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts			61789-86-4	None
			156105-31-6	None
	Amines, C11-14-branched alkyl, monohexyl and dihexyl phosphates	<1	80939-62-4	None

3.2 Additional Not applicable information

**SECTION 4. FIRST AID MEASURES** 

4.1 First aid measures

Eve contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

**Revision Date Supersedes Date** 

Page 2 of 5

6/1/2015 1/8/2014

Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before Skin contact:

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

4.2 Most important symptoms and effects, both acute and delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment available.

No further relevant information available.

## **SECTION 5. FIREFIGHTING MEASURES**

5.1 Suitable extinguishing

media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.

Unsuitable extinguishing media: Do not use direct stream of water.

5.2 Special hazards:

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

5.3 Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

6.1 Personal precautions, protective equipment and emergency procedures

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

6.3 Containment and clean-up:

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment.

### **SECTION 7. HANDLING AND STORAGE**

7.1 Handling: Keep away from heat and direct sunlight. Keep away from ignition sources - Do not smoke. Protect against electrostatic

discharges. Ensure good ventilation/exhaustion at the workplace.

See Section 8.2 for information on occupational hygiene.

Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Observe official regulations on storing 7.2 Storage:

> packagings with pressurized containers. Store away from oxidizing agents. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Rotate stock.

See Section 10 for information on conditions and materials to avoid.

7.3 End Uses: Refer to Section 1 for identified uses, and uses advised against.

## **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Butane** 

8.1 Workp	lace exposure
-----------	---------------

limits:

**Components Exposure limit and source** 

**Propane** Not available

> Long-term value = 1810 mg/m<sup>3</sup>, 750 ppm Short-term value = 1450 mg/m3, 600 ppm

Benzene, mono-C10-13-alkyl derivs., fractionation

bottoms, heavy

Zinc oxide Sulfonic acids, petroleum, calcium salts Benzenesulfonic acid, mono-C20-24-alkyl derivs.,

calcium salts

Not available

Not available

Not available Not available

Page 3 of 5 JAX BDF Cling-Lube (Aerosol)

**Revision Date Supersedes Date** 

Not an oxidizer

6/1/2015 1/8/2014

Amines, C11-14-branched alkyl, monohexyl and dihexyl Not available

phosphates

8.2 Exposure controls

**Engineering controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 Physical and chemical properties

Appearance / odor: Clear liquid / solvent odor Vapor pressure: Not available

Liquid and compressed gas in aerosol can Vapor density: **Physical state:** Not available Odor threshold: Not available Relative density: Not available

pH: Not available.

Solubility in water: Not available Melting / freezing point: Not available Partition coefficient Not available Boiling point / range: Not available (n-octanol/water):

Flash point: Not available. Product is not classified as a

> flammable aerosol. Autoignition temperature: Not available

**Evaporation rate:** Not available Decomposition temperature: Not available

Viscosity: Not available

Upper flammability limit: Not available Lower flammability limit: Not available Explosive properties: Not applicable Not available

Percent Volatile: Oxidizing properties:

9.2 Other information No further relevant information available.

#### **SECTION 10. STABILITY AND REACTIVITY**

10.1 Reactivity: See sub-sections below.

This material is stable under normal conditions. 10.2 Chemical stability:

10.3 Possibility of

Hazardous reactions are not expected to occur. hazardous reactions:

10.4 Conditions and

Keep away from heat and direct sunlight. Avoid strong oxidizers, strong alkalis and strong acids. materials to avoid:

10.5 Hazardous Carbon monoxide and carbon dioxide.

decomposition products:

## 11.1 Information on toxicological effects

LC 50 Components LD<sub>50</sub> Acute toxicity / LD<sub>50</sub> and LC<sub>50</sub> of Propane Not available Not available

ingredients:

658 mg/l/4h (inhalation, rat) **Butane** Not available Not available

Benzene, mono-C10-13-alkyl derivs., fractionation Not available

bottoms, heavy

Zinc oxide >5000 mg/kg (oral, rat) Not available Sulfonic acids, petroleum, calcium salts >5000 mg/kg (oral, rat) Not available Benzenesulfonic acid, mono-C20-24-alkyl derivs., Not available Not available

calcium salts

Amines, C11-14-branched alkyl, monohexyl and dihexyl Not available Not available

Page 4 of 5 JAX BDF Cling-Lube (Aerosol)

6/1/2015 **Revision Date** 1/8/2014 **Supersedes Date** 

phosphates

Routes of exposure: Eyes, skin, ingestion and inhalation

Other information: Not applicable

#### **SECTION 12. ECOLOGICAL INFORMATION**

L(E)C<sub>50</sub> 12.1 Toxicity: Components

> Propane Not available Butane Not available Benzene, mono-C10-13-alkyl derivs., fractionation Not available

bottoms, heavy

Zinc oxide 1.1 mg/l/96h [Oncorhynchus mykiss (rainbow trout)]

Sulfonic acids, petroleum, calcium salts >100 mg/l/48h [Daphnia magna (Water flea)]

Benzenesulfonic acid, mono-C20-24-alkyl derivs., Not available

calcium salts

Amines, C11-14-branched alkyl, monohexyl and dihexyl Not available

phosphates

**Toxicity notes:** Not available

12.2 Persistence and degradability: Not available 12.3 Bioaccumulative potential: Not available 12.4 Mobility in soil: Not available

12.5 Persistence, bioaccumulation

This product is not, or does not contain, a substance that is a PBT or a vPvB.

and toxicity for substance(s):

12.6 Other adverse effects: No adverse effects are expected.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

13.1 Waste treatment methods:

Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Consult national or regional authorities for proper disposal and reporting procedures.

## **SECTION 14. TRANSPORTATION INFORMATION**

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	Proper Shipping Name:	UN Number:	Hazard <u>Class:</u>	Packing <u>Group:</u>	Remarks:
U.S. D.O.T.	Aerosols, non-flammable	1950	2.2	None	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Aerosols, non-flammable	1950	2.2	None	Tunnel Restriction E
IMDG	Aerosols, non-flammable	1950	2.2	None	None
IATA	Aerosols, non-flammable	1950	2.2	None	None

#### **SECTION 15. REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

## **U.S. Federal Regulations:**

SARA Section 302 This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

**Extremely Hazardous** 

**Substances** 

None

SARA Section 304

Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to

reporting to the National Response Center under CERCLA: **CERCLA Hazardous** 

**Substances** 

None

Chemicals

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

TSCA Inventory

All components of this material are on the U.S. TSCA Inventory.

JAX BDF Cling-Lube (Aerosol)

Page 5 of 5

Revision Date

Revision Date 6/1/2015 Supersedes Date 1/8/2014

California Proposition

65 Status

This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California

None

Proposition 65 Listed Components

# **International Regulations:**

European Union: This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. A Chemical Safety Assessment has

not been carried out.

Canada All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in

accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.

Japan MITINot availableAustraliaNot availableSwitzerlandNot available

### **SECTION 16. OTHER INFORMATION**

Sections Revised: New SDS format

**Revision Date:** 6/1/2015

The information and recommendations contained herein are, to the best of Pressure-Lube Inc.'s knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc.'s interpretation of the available data.

\*\*\* END OF SDS \*\*\*