SAFETY DATA SHEET

1. Identification

classified (HNOC)

Supplemental information

1. Identification			
Product number	75004113		
Product identifier	PRIME SOURCE CHERRY BERRY METERED AIR FRESHENER		
Revision date	03-04-2015		
Company information	PRIME SOURCE, LLC		
	P. O. BOX 41911		
Emorgonov tolonhono US	ST LOUIS, MO 63141 United States 1-866-836-8855		
Emergency telephone US Emergency telephone outside	1-952-852-4646		
US			
Version #	02		
Supersedes date	11-05-2014		
Recommended use	Air Freshener		
Recommended restrictions	None known.		
2. Hazard(s) identification			
Physical hazards	Flammable aerosols	Category 1	
Health hazards	Serious eye damage/eye irritation	Category 2	
	Sensitization, skin	Category 1	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2	
	Hazardous to the aquatic environment, long-term hazard	Category 2	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Extremely flammable aerosol. May cause an a May cause drowsiness or dizziness.	Ilergic skin reaction. Causes serious eye irritation.	
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves. Wear eye/face protection.		
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.		
Storage	Store in a well-ventilated place. Keep container sunlight. Do not expose to temperatures exceed		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise	Static accumulating flammable liquid can beco	me electrostatically charged even in bonded and	

grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 80
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Benzaldehyde		100-52-7	1 - 2.5
Ethyl Methyl Phenylglycidate		77-83-8	0.1 - 1
Vanillin		121-33-5	0.1 - 1
Other components below reportable leve	ls		2.5 - 10

#: This substance has workplace exposure limit(s). *Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	Dermatitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal procautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clohing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unleas wearing appropriate protective (edition) containington. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significan containington. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significan spillage cancel. For personal protection, see section 8 of the SDS. Methods and materials for containment and cleaning up containment and cleaning up systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is imperable. Cover with plastic sheet to prevent spreading. Abs in vormiculite, dry sand or earth and place into containners. Following product recovery, flush ar with water. Environmental precautions Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual containnation. For vaste disposal, use section 13 of supervisory personnel of al environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge in drains, water courses or onto the ground. Use appropriate containment to avoid environmental containnation. 7. Handling and storage Precautions for safe handling Minimize fire risks from finammable and combustible materials (including combustible dust and static accumulating inju	Acetone (CAS 67-64-1)	PEL	2400 mg/m3
protective equipment and emergency procedures wareas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clohing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless waring appropriate protective clothing. Ventilat closed spaces before entring them. Use appropriate containment to avoid environmental containment and cleaning up Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (i avoid from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leads if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculie, dry sand or earth and place into containers. Following product recovery, flush an with water. Environmental precautions Avoid release to the environment. Inform appropriate managerial or suporvisory personnel of all environmental releases. Prevent further leakage or spilleging if safe to do so. Avoid discharge in drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. 7. Handling and storage Precautions for safe handling thering, pumping at high flow rates, spiash filling, creating mists or spray, tank and container filling. Lank cleaning, sampling, gauging, subich hoding, vacuum fuck operations. Pressured container: Do not plerce or burn, even after use. Bo not use if gapar buton is missing or decide Dott soging an aheter hore user missing and duron denad anuplement burding and don tarepose to tempere torial s	Components	Туре	
protective equipment and emergency procedures Iw areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clobing during clean-up. Avoid breathing mist or sapor. Do not touch damaged containers or spilled material unless waring appropriate protective clothing. Ventilat closed spaces before entring them. Use appropriate containment to avoid environmental containment and cleaning up Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (in avoid from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leads if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet the clian Wate Act and should be prevented from contaminating soil or from entering surveys presonnel of all environmental precautions Finvironmental precautions Avoid release to the environment. Inform appropriate containment to avoid environmental contamination. 7. Handling and storage Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating fluids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixin filtering, purphing at high nov rates, galan filting, creating mist or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container. Do not pierce or burn, even after use. Do not use exposor. Avoid cordata with weaks. or other sources of ignition. All equ	• •	or Air Contaminants (29 CFR 1910 1000)	
protective equipment and emergency procedures Iwa areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clohing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilat closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable contained. For personal protection, see section 8 of the SDS. Methods and materials for containment and cleaning up anxing, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, et away from spilled material is classified as a water pollutant under the Clean Wate Ard and should be prevented from containniating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Mowe the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermicultie, dry sand or earth and place into containers. Following product recovery, flush an with water. Finitions for safe handling Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquds) or dangerous reactions with incompatible materials. Handling operations that can pronote accumulation of static charges include but are not limited to: mixin filtering, pumping, auging, switch loadino, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if sprub lime radius, provident brinds industring liquds) or dangerous reactions with incompatible materials. Including cumulation of static charges include but are not limited to: mixin filtering, pumping auging high flow rates, splash filting, creating mists or v	• •	onal protection	
protective equipment and emergency procedures Iow areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local autorities should be advised if significar spillages cannot be contained. For personal protection, see section 8 of the SDS. Methods and materials for containment and cleaning up on the suitable contained. For personal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or form enteing sevage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to preven spreading. Abs in vermicuitie, dry sand or earth and place into containers. Following product recovery, flush are with water. Environmental precautions Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Precautions for safe handling operations that can promote accumulation of static charges include but are not limited to: mixin drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. 7. Handling and storage Precautions for safe handling operations t		exceeding 50°C/122 °F. Do not puncture, ind flame, heat or other sources of ignition. This cause spark and become an ignition source. equipment. These alone may be insufficient	cinerate or crush. Do not handle or store near an open material can accumulate static charge which may Avoid spark promoters. Ground/bond container and to remove static electricity. Refrigeration
protective equipment and emergency procedures low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate encitive equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventiate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significar spillages cannot be contained. For personal protection, see section 8 of the SDS. Methods and materials for containment and cleaning up away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to wateways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush ar with water. Environmental precautions Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. 7. Handling and storage Minimize fire risks from flammable and combustible materials (including combustible dust and triat cacumulating liquids) or dangerous reactions with incompatible material. Handling operations that can promote accumulation of static charges include but are not limited to: mixin filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressaurized container: Do not pierce or burn, eve			
protective equipment and emergency procedureslow areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significar spillages cannot be contained. For personal protection, see section 8 of the SDS.Methods and materials for containment and cleaning up acontainment and cleaning upRefer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (remoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc away from spilled material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush are with water.Environmental precautionsSmall Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.7. Handling and storageMinimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that c		Code in Canada, (CSA C22.1), or the Ameri 2003, "Protection Against Ignitions Arising o Fire Protection Association (NFPA) 77, "Rec	can Petroleum Institute (API) Recommended Practice ut of Static, Lightning, and Stray Currents" or National commended Practice on Static Electricity" or National
protective equipment and emergency procedureslow areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significar spillages cannot be contained. For personal protection, see section 8 of the SDS.Methods and materials for containment and cleaning upRefer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (r smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush are with water.Environmental precautionsSmall Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.Avoid release to the environment. Inform appropriate managerial or supervisory personnel of al environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge in drains, water courses or onto the ground. Use appropriate	• •	static accumulating liquids) or dangerous rea operations that can promote accumulation or filtering, pumping at high flow rates, splash f filling, tank cleaning, sampling, gauging, swit container: Do not pierce or burn, even after Do not spray on a naked flame or any other until sprayed surface is thoroughly dry. Do n heat, flame, sparks, or other sources of ignit must be grounded. Do not re-use empty con with eyes, skin, and clothing. Avoid prolonge appropriate personal protective equipment.	actions with incompatible materials. Handling f static charges include but are not limited to: mixing, illing, creating mists or sprays, tank and container tch loading, vacuum truck operations. Pressurized use. Do not use if spray button is missing or defective. incandescent material. Do not smoke while using or ot cut, weld, solder, drill, grind, or expose containers to ion. All equipment used when handling the product tainers. Avoid breathing mist or vapor. Avoid contact ed exposure. Use only in well-ventilated areas. Wear
protective equipment and emergency procedureslow areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental containment and cleaning upMethods and materials for containment and cleaning upRefer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (r smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush are with water.Environmental precautionsSmall Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.	7 Hendling and stars		
 protective equipment and emergency procedures low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental containation. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable contained for containment and cleaning up Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (n smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush are with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to 	Environmental precautions	environmental releases. Prevent further leak	age or spillage if safe to do so. Avoid discharge into
 protective equipment and emergency procedures low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significan spillages cannot be contained. For personal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (r smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc away from spilled material. This material is classified as a water pollutant under the Clean Wate Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Abs in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area 			
protective equipment and emergency procedures low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significan		smoking, flares, sparks, or flames in immedi away from spilled material. This material is or Act and should be prevented from contamina systems which lead to waterways. Stop leak safe and open area if the leak is irreparable. in vermiculite, dry sand or earth and place in	ate area). Keep combustibles (wood, paper, oil, etc.) classified as a water pollutant under the Clean Water ating soil or from entering sewage and drainage if you can do so without risk. Move the cylinder to a Cover with plastic sheet to prevent spreading. Absorb
o. Accidental release measures	protective equipment and	low areas. Remove all possible sources of ic protective equipment and clothing during cle damaged containers or spilled material unles closed spaces before entering them. Use ap contamination. Transfer by mechanical mean suitable container for recovery or safe dispos	gnition in the surrounding area. Wear appropriate ean-up. Avoid breathing mist or vapor. Do not touch ss wearing appropriate protective clothing. Ventilate propriate containment to avoid environmental ns such as vacuum truck to a salvage tank or other sal. Local authorities should be advised if significant

PEL

Propane (CAS 74-98-6)

1000 ppm

1800 mg/m3 1000 ppm

Components	Туј	oe	V	alue	
Acetone (CAS 67-64-1)	ST	EL	7	50 ppm	
	TW	/A	5	00 ppm	
Butane (CAS 106-97-8)	ST	EL	1	000 ppm	
US. NIOSH: Pocket Guid	e to Chemical Hazard	S			
Components	Туј)e	V	alue	
Acetone (CAS 67-64-1)	TW	/A	5	90 mg/m3	·
			2	50 ppm	
Butane (CAS 106-97-8)	TW	/Α	1	900 mg/m3	
			8	00 ppm	
Propane (CAS 74-98-6)	TW	/Α	1	800 mg/m3	
			1	000 ppm	
US. Workplace Environm	nental Exposure Level	(WEEL) Guides			
Components	Туј		Ň	alue	
Benzaldehyde (CAS 100-52-7)	ST	EL	1	7.4 mg/m3	
,			4	ppm	
	TW	Ά	8	.7 mg/m3	
			2	ppm	
Vanillin (CAS 121-33-5)	TW	/Α	1	0 mg/m3	
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
* - For sampling details, pl					
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.				
ividual protection measur	es, such as personal	protective equipme	ent		
Eye/face protection	Chemical respirat	or with organic vapo	r cartridge and	full facepiece.	
Hand protection	Wear appropriate	chemical resistant g	loves.		
Skin protection					
Other	Wear appropriate	chemical resistant c	lothing.		
Respiratory protection	Chemical respirat	or with organic vapo	r cartridge and	full facepiece.	
Thermal hazards	Wear appropriate	thermal protective c	lothing, when n	ecessary.	
neral hygiene Isiderations	after handling the clothing and prote	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should no be allowed out of the workplace.			
Physical and chemic	al properties				
pearance					

Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated

Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.9 % estimated
Flammability limit - upper (%)	9.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	55 psig @70F estimated
Vapor density	Not available.
Relative density	0.197 g/cm3 estimated
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.20 g/cm3 estimated
Flammability class	Flammable IB estimated
Heat of combustion (NFPA 30B)	30.32 kJ/g estimated
Percent volatile	98.27 % estimated
Specific gravity	0.197 estimated
VOC (Weight %)	28.66 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristic	Dermatitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.
Information on toxicologica	l effects

Information on toxicological effects

Acute toxicity

Narcotic effects. May cause an allergic skin reaction.

pig	 > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 1 - 5 mg/l, 4 Hours 		
pig	 > 9.4 ml/kg, 24 Hours > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 		
pig	 > 9.4 ml/kg, 24 Hours > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 		
pig	 > 9.4 ml/kg, 24 Hours > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 		
	 > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 		
	 > 9.4 ml/kg, 24 Hours 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg 		
	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg		
	132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg		
	132 mg/l, 3 Hours 50.1 mg/l 5800 mg/kg 2.2 ml/kg		
	50.1 mg/l 5800 mg/kg 2.2 ml/kg		
	5800 mg/kg 2.2 ml/kg		
	2.2 ml/kg		
	2.2 ml/kg		
	1 - 5 mg/l, 4 Hours		
	1 - 5 mg/l, 4 Hours		
	1 - 5 mg/l, 4 Hours		
	1 - 5 mg/l, 4 Hours		
	1.43 ml/kg		
	1237 mg/l, 120 Minutes		
	52 %, 120 Minutes		
	1355 mg/l		
	1237 mg/l, 120 Minutes		
	52 %, 120 Minutes		
	1355 mg/l		
	658 mg/l/4h		
	> 2000 mg/kg, 24 Hours		
additional component data not shown.			
skin contact may cause temporary irritatio	n.		
erious eye irritation.			
ble.			
	ents present at greater than 0.1% are		
e an allergic skin reaction. vailable to indicate product or any compone	IARC, ACGIH, NTP, or OSHA.		
e an allergic skin reaction. vailable to indicate product or any compone or genotoxic.	ated Substances (29 CFR 1910.1001-1050)		
se	able. se an allergic skin reaction. available to indicate product or any compon- ic or genotoxic. duct is not considered to be a carcinogen by		

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Toxic to a	aquatic life with long lasting effects.		
Product		Species	Test Results	
7 OZ PRIME SRC CHERRY	BERRY LB	12PK (CAS Mixture)		
Aquatic				
Crustacea	EC50	Daphnia	7406.3755 mg/l, 48 hours estimated	
Fish	LC50	Fish	12113.5684 mg/l, 96 hours estimated	
Components		Species	Test Results	
Acetone (CAS 67-64-1)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Benzaldehyde (CAS 100-52-	7)			
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	0.8 - 1.44 mg/l, 96 hours	
Vanillin (CAS 121-33-5)				
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promelas)	53 - 61.3 mg/l, 96 hours	
* Estimates for product may	be based on	additional component data not shown.		
ersistence and degradability		s available on the degradability of this product.		
Bioaccumulative potential	No data available.			
Partition coefficient n-octa				
Acetone	(-0.24		
Benzaldehyde		1.48		
Butane Propane		2.89		
Vanillin		2.36 1.37		
lobility in soil	No data a	available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
3. Disposal consideratio	ons			
Disposal instructions	under pre sewers/w	nd reclaim or dispose in sealed containers at lic essure. Do not puncture, incinerate or crush. Do vater supplies. Do not contaminate ponds, water . Dispose of contents/container in accordance v ns.	o not allow this material to drain into rways or ditches with chemical or used	
ocal disposal regulations	Dispose i	in accordance with all applicable regulations.		
lazardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
US RCRA Hazardous Wast	e U List: Re	ference		
Acetone (CAS 67-64-1)		U002		
Nooto from readduge / wassed	Dianaca	of in accordance with least requisions. Example	antoinara ar linara may ratain aama	

Waste from residues / unused	Dispose of in accordance with local regulations. Empty containers or liners may retain some
products	product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
00	

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
· ·	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	This substance/mixture is not intended to be transported in bulk.
Annex II of MARPOL 73/78 and	
the IBC Code	







DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

15. Regulatory informatio	n		
US federal regulations	This product is a "Hazardou Standard, 29 CFR 1910.120 All components are on the U	00.	ned by the OSHA Hazard Communication
TSCA Section 12(b) Export	Notification (40 CFR 707, Su	lbpt. D)	
Not regulated.			
CERCLA Hazardous Substa	nce List (40 CFR 302.4)		
Acetone (CAS 67-64-1)		Listed.	
SARA 304 Emergency relea	se notification		
Not regulated.			
OSHA Specifically Regulate	ed Substances (29 CFR 1910	.1001-1050)	
Not listed.			
Superfund Amendments and Re	authorization Act of 1986 (S	ARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazar	dous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name		CAS number	% by wt.
Cinnamal		104-55-2	0.01 - 0.1
gamma-Undecalactone		104-67-6	0.01 - 0.1

Product name: 7 OZ PRIME SRC CHERRY BERRY LB 12PK Product #: 1000013600 Version #: 02 Revision date: 03-04-2015 Issue date: 08-21-2014

		CAS number	% by wt.
Methyleugenol Safrole		93-15-2 94-59-7	0.01 - 0.1 0.01 - 0.1
her federal regulations			
Clean Air Act (CAA) Section	on 112 Hazardous Air Po	llutants (HAPs) List	
Not regulated. Clean Air Act (CAA) Section	on 112(r) Accidental Rele	ease Prevention (40 CFR	68 130)
Butane (CAS 106-97-8) Propane (CAS 74-98-6))		
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Ad Chemical Code Numb		2, Essential Chemicals (ź	21 CFR 1310.02(b) and 1310.04(f)(2) and
Acetone (CAS 67-6		6532	
			Mixtures (21 CFR 1310.12(c))
Benzaldehyde (CA		50 %WV	
Acetone (CAS 67-6	o4-1) Il Mixtures Code Numbe	. 35 %WV	
Acetone (CAS 67-6		6532	
Benzaldehyde (CA	,	8256	
S state regulations			
US. Massachusetts RTK -	Substance List		
Acetone (CAS 67-64-1))		
Benzaldehyde (CAS 10			
Butane (CAS 106-97-8) Propane (CAS 74-98-6)			
US. New Jersey Worker a		(now Act	
Acetone (CAS 67-64-1)			
Benzaldehyde (CAS 10 Butane (CAS 106-97-8) Propane (CAS 74-98-6	10-52-7))		
US. Pennsylvania Worker		-Know Law	
Acetone (CAS 67-64-1) Benzaldehyde (CAS 10 Butane (CAS 106-97-8) Propane (CAS 74-98-6 US. Rhode Island RTK	10-52-7))		
Acetone (CAS 67-64-1) Butane (CAS 106-97-8))		
Propane (CAS 74-98-6	65		
US. California Proposition		wn to the State of Californ	ia to cause cancer.
US. California Proposition WARNING: This produce	ct contains a chemical kno		
US. California Proposition WARNING: This produce	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2)		1ce 29, 1999 er 16, 2001
US. California Proposition WARNING: This produc US - California Propos Estragole (CAS 14 Methyleugenol (CA	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2)	te/Carcinogenic substar Listed: October 2 Listed: Novembe	1ce 29, 1999 er 16, 2001
US. California Proposition WARNING: This product US - California Propose Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2) 9-7)	te/Carcinogenic substar Listed: October 2 Listed: Novembe	1ce 29, 1999 er 16, 2001 1, 1988
US. California Proposition WARNING: This produc US - California Propos Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-55	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2) 9-7) Inventory name	te/Carcinogenic substar Listed: October 2 Listed: Novembe	nce 29, 1999 er 16, 2001 1, 1988 On inventory (yes/no
US. California Proposition WARNING: This produc US - California Propos Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59 ternational Inventories Country(s) or region	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2) 9-7) Inventory name	te/Carcinogenic substan Listed: October 2 Listed: Novembe Listed: January 7	nce 29, 1999 er 16, 2001 1, 1988 On inventory (yes/no
US. California Proposition WARNING: This product US - California Propose Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59 ternational Inventories Country(s) or region Australia	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2) 9-7) Inventory name Australian Inventory o	te/Carcinogenic substan Listed: October 2 Listed: Novembe Listed: January 7 ⁵ Chemical Substances (A List (DSL)	nce 29, 1999 er 16, 2001 1, 1988 On inventory (yes/no ICS) Y
US. California Proposition WARNING: This product US - California Propose Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59 ternational Inventories Country(s) or region Australia Canada	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) \S 93-15-2) 9-7) Inventory name Australian Inventory o Domestic Substances Non-Domestic Substa	te/Carcinogenic substan Listed: October 2 Listed: November Listed: January 7 Chemical Substances (Al List (DSL) nces List (NDSL)	nce 29, 1999 er 16, 2001 1, 1988 On inventory (yes/nd ICS) Y
US. California Proposition WARNING: This produce US - California Proposi Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59 Country(s) or region Australia Canada Canada	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) (S 93-15-2) 9-7) Inventory name Australian Inventory o Domestic Substances Non-Domestic Substa Inventory of Existing C	te/Carcinogenic substan Listed: October 2 Listed: November Listed: January 7 Chemical Substances (Al List (DSL) Inces List (NDSL) Chemical Substances in Ch Existing Commercial Che	nce 29, 1999 er 16, 2001 1, 1988 ICS) Y Y nina (IECSC) Y
US. California Proposition WARNING: This produce US - California Propose Estragole (CAS 14 Methyleugenol (CA Safrole (CAS 94-59 cernational Inventories Country(s) or region Australia Canada Canada China	ct contains a chemical kno sition 65 - CRT: Listed da 0-67-0) (S 93-15-2) 9-7) Inventory name Australian Inventory o Domestic Substances Non-Domestic Substan Inventory of Existing C European Inventory of Substances (EINECS)	te/Carcinogenic substan Listed: October 2 Listed: November Listed: January 7 Chemical Substances (Al List (DSL) Inces List (NDSL) Chemical Substances in Ch Existing Commercial Che	nce 29, 1999 er 16, 2001 1, 1988 ICS) Y hina (IECSC) Y mical Y

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date Version #	08-21-2014 03-04-2015 02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names GHS: Classification