

SAFETY DATA SHEET

1. Identification

Product number 75004150
Product identifier 18 OZ PRIME SOURCE SPARK OVEN & GRILL CLNR
Revision date 05-20-2014
Company information Prime Source, LLC
P. O. Box 41911
Saint Louis, MO 63141 United States
Company phone 1-800-444-2002
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 05-12-2014
Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes severe skin burns and eye damage. Causes serious eye damage.

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Not classified.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Hazardous components			
Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Diethylene Glycol Monobutyl Ether		112-34-5	2.5 - 10
Sodium Hydroxide		1310-73-2	2.5 - 10

Hazardous components			
Chemical name	Common name and synonyms	CAS number	%
1,2-Propanediol		57-55-6	1 - 2.5
Propane		74-98-6	1 - 2.5
Triethanolamine		102-71-6	1 - 2.5
Other components below reportable levels			80 - 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Immediately flush skin with plenty of water. Chemical burns must be treated by a physician. Call a physician or poison control center immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Have victim rinse mouth thoroughly with water. Call a physician or poison control center immediately. Get medical attention immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Corrosive effects. May cause temporary blindness and severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. In case of shortness of breath, give oxygen. Keep victim warm. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Clean contaminated surface thoroughly. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Will ignite if exposed to intensive heat or open air. Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Wear self-contained breathing apparatus and protective suit. Observe good industrial hygiene practices. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol. Store locked up. Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Keep the container dry. Keep this material away from food, drink and animal feed. Store away from incompatible materials (see Section 10 of the MSDS). Level 1 Aerosol (NFPA 30B)

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	PEL	2 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear chemical goggles and face shield. Do not get this material in contact with eyes.
Hand protection	Wear protective gloves.
Other	Do not get this material in contact with skin. Wear chemical protective equipment that is specifically recommended by the manufacturer.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Do not get this material in contact with eyes. When using, do not eat, drink or smoke. Do not get this material on clothing. Do not get this material in contact with skin. Avoid contact with eyes. Avoid contact with skin. When using do not eat or drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Compressed liquefied gas.
Color	Pale yellow
Form	Aerosol.
Physical state	Gas.
Boiling point	323.6 °F (162 °C) estimated
Flash point	-156.00 °F (-104.44 °C) Propellant estimated
Melting point/freezing point	Not available.
Odor	Not established.
pH	13.5 - 14.5 estimated
Solubility(ies)	Not available.
Vapor density	Not available.
Vapor pressure	60 - 70 psig @ 70 F estimated
Viscosity	Not available.
Other information	
Specific gravity	1.01 estimated estimated

10. Stability and reactivity

Reactivity	Strong acids.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air. Avoid temperatures exceeding the flash point. This product may react with oxidizing agents. Do not mix with other chemicals.
Hazardous decomposition products	May include oxides of oxides of carbon. May include oxides of phosphorus.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Causes digestive tract burns.
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.
Eye contact	Causes severe eye burns. Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Information on toxicological effects	
Acute toxicity	Acute LD50: 18615 mg/kg, Rat, Dermal Acute LC50: 574 mg/l/4h, Rat, Inhalation Causes burns.

Product	Species	Test Results
18 OZ PRIME SOURCE OVEN GRL CLNR LB 12PK (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	75459.25 ml/kg, estimated
		12175.0879 mg/kg, estimated
	Rat	18615 mg/kg
<i>Inhalation</i>		
LC50	Mouse	19359.4316 mg/l, 2 Hours, estimated
	Rat	96998.1172 mg/l, 15 Minutes, estimated
		18733.0957 mg/l, 4 Hours, estimated
		574 mg/l/4h
LD50	Rat	442.1053 µg/m3, If <1L: Consumer Commodity hr, estimated
<i>Oral</i>		
LD50	Dog	952.381 g/kg, estimated
	Guinea pig	57313.5 mg/kg, estimated
	Mouse	79946.7031 mg/kg, estimated
	Rabbit	73284.4766 mg/kg, estimated
	Rat	
		29.4579 g/kg, estimated
<i>Other</i>		
LD50	Mouse	809.6043 mg/kg, estimated
	Rat	15836.3096 mg/kg, estimated
Components	Species	Test Results
1,2-Propanediol (CAS 57-55-6)		
Acute		
<i>Oral</i>		
LD50	Dog	19 g/kg
	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg
<i>Other</i>		
LD50	Mouse	6630 mg/kg
	Rat	6423 mg/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2700 mg/kg
<i>Oral</i>		
LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	4500 mg/kg
<i>Other</i>		
LD50	Mouse	850 mg/kg
	Rat	500 mg/kg

Components	Species	Test Results
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l/4h
Sodium Hydroxide (CAS 1310-73-2)		
Acute		
<i>Dermal</i>		
LD50	Rat	1350 mg/kg
<i>Other</i>		
LD50	Mouse	40 mg/kg
Triethanolamine (CAS 102-71-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 20000 mg/kg
<i>Oral</i>		
LD50	Guinea pig	5300 mg/kg
	Rat	8 g/kg
<i>Other</i>		
LD50	Mouse	1450 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes severe eye burns. Causes serious eye damage.
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	Not expected to be hazardous by OSHA criteria.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Triethanolamine (CAS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Not expected to be hazardous by OSHA criteria.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin. Prolonged exposure may cause chronic effects.
	Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity	LC50: 926 mg/L, Fish, 96.00 Hours EC50: 68060 mg/L, Daphnia, 48.00 Hours IC50: 7426 mg/L, Algae, 72.00 Hours Components of this product have been identified as having potential environmental concerns.
--------------------	---

Product	Species	Test Results
18 OZ PRIME SOURCE OVEN GRL CLNR LB 12PK (CAS Mixture)		
Algae	IC50	Algae 7426 mg/L, 72 Hours
Crustacea	EC50	Daphnia 68060 mg/L, 48 Hours
Fish	LC50	Fish 926 mg/L, 96 Hours

Components		Species	Test Results
1,2-Propanediol (CAS 57-55-6)			
Crustacea	EC50	Daphnia	10000.0001 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	710 mg/l, 96 hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Sodium Hydroxide (CAS 1310-73-2)			
Fish	LC50	Fish	45, 96 Hours
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Western mosquitofish (Gambusia affinis)	125 mg/l, 96 hours
Triethanolamine (CAS 102-71-6)			
Algae	IC50	Algae	216 mg/L, 72 Hours
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	10610 - 13010 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Diethylene Glycol Monobutyl Ether	0.56
1,2-Propanediol	-0.92
Triethanolamine	-1
Propane	2.36
Butane	2.89

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose of contents/container in accordance with local/regional/national/international regulation.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Subsidiary class(es)	Not available.
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Labels required	None
Special provisions	N82
Packaging exceptions	306

Packaging non bulk None

Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable, containing substances in Class 8, Packing Group III

Transport hazard class(es) 2.1

Subsidiary class(es) 8

Packaging group Not available.

Environmental hazards No

Labels required 2.1, 8

ERG Code 10C

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950

UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1

Subsidiary class(es) 8

Packaging group Not available.

Environmental hazards

Marine pollutant No

Labels required 2.1, 8

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium Hydroxide (CAS 1310-73-2)

LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed.

Food and Drug Administration (FDA) Not regulated.

US state regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) 500 lbs

Propane (CAS 74-98-6) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

1,2-Propanediol (CAS 57-55-6)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Hydroxide (CAS 1310-73-2)

Triethanolamine (CAS 102-71-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-12-2014

Product name: 18 OZ PRIME SOURCE OVEN GRL CLNR LB 12PK

SDS US

Product #: 1000013552 Version #: 02 Revision date: 05-20-2014 Issue date: 05-12-2014

9 / 10

Revision date	05-20-2014
Version #	02
Further information	Not available.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Transport Information: Material Transportation Information